

NT 644



Value	Tol. +	Tol. -	Offset
120,00 Ohm	10,0 %	10,0 %	
1,00 kOhm	10,0 %	10,0 %	
1,00 MOhm	10,0 %	10,0 %	
Vf	Tol. +	Tol. -	I max.
Vz	Tol. +	Tol. -	I max.
5,10 V	10,0 %	10,0 %	
Value	Tol. +	Tol. -	Offset
1,00 nF	300,0 %	10,0 %	
220,00 nF	10,0 %	10,0 %	
10,00 µF	10,0 %	10,0 %	
Vf	Tol. +	Tol. -	Vr max.
			20,00 V
Varistor V	Tol. +	Tol. -	Oper. V
390,00 V	10,0 %	10,0 %	

2150 VDC
1500 VAC

NT 644 High voltage wiring tester

- ▶ Easy operation via PC with control software NT Control
- ▶ Extensive result reporting to file, to printer or via database connection*
- ▶ Extensive display possibilities and tools for the fault location in the unit under test
- ▶ Up to 1024 test points
- ▶ Insulation test up to 2150 VDC
- ▶ Dielectric strength test up to 1500 VAC
- ▶ Continuity test, short circuit test and component test
- ▶ Remote maintenance via network

High voltage tester 2150 VDC and 1500 VAC at an affordable price

- ▶ Solid 19" housing
- ▶ Expandable by several measurement electronics

Ensuring of your product quality by high system availability

The high reliability of the adaptronic test and adapter systems, our quick response service and more than 30 years of experience make a convincing contribution to the quality assurance of your products.

* optional