Schleuniger



ToolingShuttle 30Mobile Quick-Change Unit for CrimpCenter Series

OPTIONS

ToolingShuttle 30

Concept

The ToolingShuttle 30 combines the crimp applicator (tooling), terminal reel and paper winder into one mobile quick-change unit for CrimpCenter 3-series fully automatic crimping machines. The ToolingShuttle 30 allows the operator to exchange all three elements simultaneously which significantly reduces changeover time. The ToolingShuttle 30 can be prepared for the next job at an external workstation while the machine is producing thereby reducing machine downtime to a minimum. Once in position the applicator is quickly moved from the ToolingShuttle 30 and secured into the crimping station. The ToolingShuttle 30 accepts most all standard crimping tools (mini-style applicators), so existing applicators can be easily integrated.

Plug & Crimp™ Technology

Innovative Plug & Crimp technology lets operators exchange ToolingShuttles on CrimpCenter series machines in the shortest possible time – without any additional tools. The ToolingShuttle 30 is a sturdy lightweight construction equipped with 2 wheels and a handle for optimum maneuverability.

Options

- ShuttleRack: Mobile storage rack for up to 5 ToolingShuttle 30 units
- Automatic barcode identification of individual ToolingShuttle 30 with barcode

Technical specifications	
Length	660 mm (with terminal reel)* (26.0")
Width	140 mm (5.5")
Height	1107 mm (with crimp applicator)* (43.5")
Weight	Base frame: 7 kg (15.4 lbs.) Fully equipped: 11.5 kg* (25.3 lbs.)
CE-Conformity	The ToolingShuttle 30 installed on CrimpCenter fully automatic machines complies with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important Notice	Schleuniger recommends that wire samples be submitted in cases here there is doubt as to processing capabilities of a particular machine.

^{*} Dimensions and weight may vary depending on type of crimp applicator, terminal reel and paper winder.