



TROMBOI 2003

This unwinder impresses with its manual hydraulic pump and a very robust construction, which allows the unwinding of heavy drums. The range of application extends from winding good processing on building sites over cable installation to the storage and shipping area.

The sturdy axle holders have to be inserted and locked in a height suitable for the workable drum dimension.

The drum axle has to be positioned to the drum height. After having been rolled into the axle holder the drum has to be lifted by using the manual hydraulic pump. Drum is lowered via the vent screw. (Only suitable for indoor use)

TROMBOI 2003

Unwinder with manual hydraulic pump for drums of up to Ø 2000 mm and drum weight of 4000 kg

Part No. 85005091

Drum-Ø	900 - 2000 mm
Drum axle with adjusting rings	Ø 76 x 1700 mm
Drum weight	max. 4000 kg
L x W x H	approx. 550 x 300 x 1520 mm
Colour	RAL 7005, mouse grey
Weight (incl. axles and cones)	approx. 132 kg / pair

Additional axles

Ø 34 x 1140 mm, Loading capacity max. 700 kg	Part No. 85008020
Ø 60 x 1140 mm, Loading capacity max. 1700 kg	Part No. 85008030
Ø 60 x 1340 mm, Loading capacity max. 1800 kg	Part No. 85008040